

Universal 5-Gallon Spill Kit #SPKU-5 - Absorbs up to 4.6 Gallons



Be prepared for fast response with a variety of sorbents!

- Packed with SpillTech pads and socks to quickly contain and absorb spills of oils, coolants, solvents and water
- 5-gallon Overpack container is durable, lightweight and weather and chemical resistant
- Includes disposal bags, ties, goggles, gloves and tamperproof seal labels for safe cleanup

SPKU-5 Specifications

Dimensions:	ext. dia. 12" x 16.75" H
Shipping	13.4" W x 13.4" L x 17.25" H
Dimensions:	
Sold as:	1 per package
Absorbency:	Up to 4.6 gal. per package
Weight:	11.34 lbs.
# per Pallet:	24
Incinerable:	No
Ship Class:	175
Includes:	10 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 2 - 3" x 4' Gray Universal Sorbent Socks (GSO430) 2 - 18" X 30" Yellow Disposal Bag & Tie (A-DISP BAG-SM) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 1 - 12" x 16.75" White 5-Gallon OverPack (1H2/Y1.5/30) (A5OVER) 6 - 6" x 2" TamperProof Seals (A-SEAL)

Metric Equivalent Specifications

Dimensions:	ext. dia. 30.5cm x 42.5cm H
Shipping	34cm W x 34cm L x 43.8cm H
Dimensions:	
Absorbency:	Up to 17.4 L per package
Weight:	5.1 kg

SPKU-5 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com